

FAY, SHARPE, BEALL, FAGAN, MINNICH & MCKEE

THOMAS E. BEALL, JR.*
CHRISTOPHER B. FAGAN*
RICHARD M. KLEIN*
THOMAS E. KOCOVSKI, JR.
SHRINATH MALUR*†
JOHN R. MATTINGLY*†
JAMES W. MCKEE*
RICHARD J. MINNICH*
JAY F. MOLDOVANYI
PHILIP J. MOY, JR.*†
TIMOTHY E. NAUMAN*
PATRICK R. ROCHE*
ALBERT P. SHARPE, III*
DANIEL J. STANGER
SANDRA M. KOENIG*
MARK S. SVAT*
JUDE A. FRY*
JOSEPH D. DREHER*
SUE ELLEN PHILLIPS*
SCOTT A. MCCOLLISTER*

PETAR KRAGULJAC*
COLLEEN FLYNN GOSS*
A. JOHN DEMARCO
BRIAN E. KONDAS
STEVEN M. AUUIL
R. SCOTT SPEROFF
JOHN F. ROLLINS
CINDY A. CHERICHETTI
STEVEN M. HAAS
DANIEL G. BLACKHURST*
GENE W. STOCKMANT
Of Counsel

JEFFREY M. KETCHUM
Registered Patent Agent

* Bar Membership Other Than Virginia
† Bar Membership in District of Columbia

ATTORNEYS AT LAW

104 EAST HUME AVENUE
ALEXANDRIA, VIRGINIA 22301

(703) 684-1120

PATENT, TRADEMARK
AND COPYRIGHT LAW

FACSIMILE: (703) 684-1157
E-MAIL: fsb@alex.dgsys.com

OHIO OFFICE
1100 SUPERIOR AVENUE, SUITE 700
CLEVELAND, OHIO 44114
(216) 861-5582

Date: July 3, 1997

Attorney Docket No. BAY-210

To: Assistant Commissioner for Patents
Washington, D.C. 20231

Sir: Transmitted herewith for filing is the patent application of:

Inventor: BAYCHAR

For:
WATERPROOF/BREATHABLE MOISTURE TRANSFER
LINER FOR IN-LINE SKATES AND THE LIKE

***THIS IS A
CONTINUATION-IN-PART
APPLICATION OF SERIAL
NO. 08/813,438, FILED
MARCH 10, 1997, WHICH
IS A CONTINUATION-IN-PART
OF SERIAL NO. 08/747,340,
FILED NOVEMBER 12, 1996**

68895 U.S. PTO
08/887847
07/03/97

Enclosed are:

- ☒ 11 Sheets of Drawings
- ☐ This application is being filed without an executed Declaration, which will be filed later in accordance with 37 CFR 1.53 (d).
- Priority is claimed from _____ Application No. _____
filed _____ ☐ A certified copy is attached herewith.
- Copies of the disclosure documents listed on the attached PTO 1449 form and
☐ discussed in the specification or ☐ attached Information Disclosure Statement.
- ☒ A verified statement to establish small entity status under 37 CFR 1.9 and 1.27.
- ☒ Specification: Abstract ☒ , Description 26 pages; and 7 claim(s).
- ☐ Preliminary Amendment.
- ☒ Executed Declaration.

The filing fee is calculated as shown below:

For:	No. Filed	No. Extra
Basic Fee		
Total Claims	7 - 20 = *	0
Indep Claims	1 - 3 = *	0
<input type="checkbox"/> Multiple Dependent Claim (s)		

* If difference is less than zero
then enter '0' in second column

Small Entity

Rate	Fee
	\$ 385
x 11	\$ 0
x 40	\$ 0
+ 130	\$ 0
Total	\$ 385

Large Entity

Rate	Fee
	\$ 770
x 22	\$
x 80	\$
+ 260	\$
Total	\$

OR

☒ A check in the amount of \$ 385.00 is enclosed for the filing fee.

☒ The Commissioner is hereby authorized to charge any additional fees that may be required to Deposit Account No. 02-1540. A duplicate of this sheet is attached.

Respectfully Submitted,

By: Shrinath Malur
Registration No. 34,663

66605 U.S. PTO 08/887847 07/03/97

BAY-210

Title of the Invention

WATERPROOF/BREATHABLE MOISTURE TRANSFER LINER FOR IN-LINE
SKATES AND THE LIKE

Inventor

Baychar

09437847 "070397
/650/0" /48/8880

**WATERPROOF/BREATHABLE MOISTURE TRANSFER LINER FOR IN-LINE
SKATES AND THE LIKE**

FIELD OF THE INVENTION

The present invention relates to liners used in a variety of application. For example, the liner of the present invention may be employed in a variety of applications including in-line skates (shell and soft boot) and the like. The liner is breathable and waterproof to increase comfort for the skater.

BACKGROUND OF THE INVENTION

Various types of liners are known in the prior art. These liners are designed to provide certain levels of comfort and durability. Furthermore, in-line skates are also well known in the art as evidenced by U.S. Patent Nos. 5,340,132, 5,397,141 and 5,437,466. Of these patents, only U.S. Patent No. 5,437,466 discloses what is commonly referred to as a "soft-boot". In other words, the shoe body is made of a soft, pliable material. General statements are provided about the materials used for the shoe body, but not in great detail.

However, the liners and in-line skates, as well as snowboard boots, etc., known in the art do not provide the advantages realized by the present invention. With the art of in-line skating becoming increasing recreational, numerous categories of skaters are developing in large numbers. The present inventor has recognized the problems faced by the

aggressive and the recreational categories of skaters and has developed a liners to overcome such problems.

There is an ongoing need for comfort, breathability and support for both removable liners as well as soft boot liners. In prior removable liner designs, the conventional liner is often constructed with rigid, non-breathable outer materials, such as vinyl's, foams and nylons. The inner liners have been leather, nylon or polyester blends which extremely limited the ability to breathe or wick moisture away from a skater's body. These materials have prevented the foot from breathing adequately. In the case of "shell boot" skates, the plastic material that forms the outer shell boot structure holds the heat and moisture inside the boot. As a result, the lining becomes saturated with sweat which adversely affects the skater's comfort and performance level. This problem is even worse with the aggressive skaters whose needs for proper ventilation are even greater.

SUMMARY OF THE INVENTION

An object of the present invention is to provide lining system employing a cooler and more breathable liner that meets the needs of each individual skater. Accordingly, the liner of the present invention can be accommodated to the needs of skaters of various skill categories by permitting the inner liner material, which is against the foot, to vary in fiber content and construction.

This object of the present invention is realized by providing a lining system having lining materials which act as a moisture transfer system. Moisture vapors are transferred through the liner from one side to the other side. This is accomplished by utilizing certain materials in a manner determined by the inventor after considerable experimentation and effort. The details of the specific materials as used in the combination are disclosed in the Detailed Description of the Preferred Embodiments.

The moisture transferring lining system of the present invention overcomes the problems in the prior art lining systems and liners and meets the needs of even the most aggressive skaters.

Various other objects, features and advantages of the present invention will become readily apparent in view of the following detailed description of the preferred embodiments in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a first portion of the liner according to a first embodiment of the present invention.

Figure 2 illustrates a second portion of the liner according to a first embodiment of the present invention.

Figure 3 illustrates an example of the liner according to the first embodiment of the present invention.

Figure 4 illustrates the liner shown in Figure 3 as applied to an inline skate.

Figures 5(a) and 5(b) illustrate a sole portion of a shoe constructed according to a preferred embodiment of the present invention.

Figures 6 and 7 illustrate a tongue portion of a shoe constructed according to a first embodiment of the present invention.

Figure 8 illustrates a more detailed view of the liner portion used for the tongue of Figures 6 and 7.

Figure 9 illustrates a portion of the liner used in the upper cuff area.

Figure 10 illustrates the travel of moisture through a reticulated foam then a flexible mesh and into and through a breathable membrane according to the first embodiment of the present invention.

Figure 11 illustrates the toe portion of a shoe according to a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following detailed description of the preferred embodiments of the present invention is undertaken in connection with the drawings. This description, while undertaken with respect to the disclosed embodiments, is intended to enable a variety of different applications and slight modifications which form a part of the present invention. More specifically, many of the materials used in this lining system have been developed relatively recently, and in many cases are still being modified and improved.

Where possible, tradenames of specific products have been used to assist in the understanding of the invention. The lining system according to the present invention can be easily adapted to accommodate further developments in these materials. With this in mind, the preferred embodiments currently envisioned are set forth below.

Figure 1 illustrates a portion of the liner, or lining system, according to a first embodiment of the present invention. As shown in Figure 1, a first foam material 20 is provided between an inner liner 10 and a second foam material 30. The inner liner 10 can be attached to the first foam material 20 by lamination, stitch or ultra sonically bonded or the like. The second foam material 30 is a germicidal antimicrobial reticulated and/or hydrophilic open cell foam and has a thickness of approximately $\frac{1}{4}$ inch. The first foam material is also preferably germicidal reticulated or open cell hydrophilic and has a thickness of approximately $\frac{1}{16}$ to $\frac{1}{8}$ inch. All of the foam materials used in the present invention are assumed to be breathable and their thicknesses variable. Depending upon the application, some of the foam materials may not be used and the thickness of any foam material that is used can be changed as needed. For example, a foam called Aquazone by Foamex, Comfortemp by Frisby or Netsorb by Vita Olympic or the like can be used. Preferably, the germicidal antimicrobial hydrophilic or reticulated foam is attached to a nonwoven top sheet made of lycra, wood pulp and cotton, polypropylene, polyester, or rayon or a

combination thereof. Otherwise, this two part structure can be replaced with an elastomeric composite having a foam with a nonwoven top sheet formed in a single process. Preferably, in either case, the nonwoven top sheet is one manufactured by Dupont (Sontara Technology nonwoven), Dexter Synthetics, Veritex, Nordlys or the like.

The inner liner fabric is a moisture transfer fabric capable of wicking moisture. The inner liner 10 is preferably constructed using specific fabrics possessing certain desired characteristics, but with varying fiber compositions. A list of fabrics which can be employed depending upon the individual needs of their application as well as the individual needs of each skater are provided below. These fabrics may either be used individually or in combination. The following inner moisture transfer liner 10 materials may also be replaced by new moisture transfer fabrics with similar characteristics as the technology on the market develops for this invention.

The first fabric is an antimicrobial, antifungal polypropylene (also referred to as polyolefin) lycra blend (2%) with INNOVA fiber, or the like. INNOVA is a continuous filament fiber (manufactured by Deercreek Fabrics, Inc. or Menra Mills).

The second fabric is an antimicrobial, antifungal polypropylene having a polyester or cotton backing or the like (such as that manufactured by Coville, Inc.). This fabric has the face of one fiber and the backing of another and may vary

in composition depending on the performance level of the skater.

The third fabric is an antimicrobial, antifungal polypropylene/cotton blend with ALPHA fiber, or the like (such as that manufactured by Intex Fabric, Inc.).

The fourth fabric is a field sensor polyester with waffle weave construction (such as that distributed by Yagi & Co., Inc. and manufactured by Toray). This fabric is constructed to transfer moisture immediately away from the foot and performs best as the liner for the soft boot in-line skate. Alternatively, a polyester material known as Aqua-Dry, distributed by Teijin Shojin can be employed or the like.

The fifth fabric is a hydrophilic, antimicrobial Dri-lex Baby Kid or perforated material (such as that manufactured by Faytex Corp.).

The sixth fabric is a polyester looped Terry (such as that manufactured by Kronfli Spundale Mills, Inc.).

The seventh fabric is a sueded/sanded polyester microfiber material (such as that distributed by Yagi & Co., Inc. and Teijin Shojin, Inc., Miliken or Malden Mills).

The eighth fabric is an antimicrobial, antifungal Polar Tec Series 2000, which is a wickable, moisture transfer fiber, containing lycra, polypropylene, or the like.

Finally, the ninth fabric is Shoeller Dryskin 61487, or the like.

All of these fabrics have good moisture transfer characteristics which prevent damage to a skater's foot by

preventing excessive moisture built-up. The moisture transfer inner fabrics may vary in composition and structure in this liner system as fiber technology advances.

The moisture transfer characteristics of the inner liner 10 causes moisture vapors to be passed from a skater's body through the inner liner 10 where it then comes into contact with the first foam material 20. The moisture vapors travel through the first foam material 20 and come into contact with the abutting second foam material 30.

As discussed above, first foam material 20 may be a cellular elastomeric composite comprised of a layer of germicidal antimicrobial open cell hydrophilic polyurethane foam such as Aquazone and a nonwoven top sheet. All of the foam materials discussed herein are preferably polyurethane, although not specifically mentioned each time. The inclusive top sheet is preferably composed of lycra, wood pulp, rayon, cotton, polypropylene, polyester, or a combination thereof. Alternatively, foam material 20 can be a foam that is separate from the nonwoven top sheet and is attached to the nonwoven top sheet by lamination, stitch bonding or the like. The nonwoven top sheet (when used) abuts the next layer of 1/4" reticulated and/or open cell hydrophilic foam, or second foam material 30, The second foam material 30 may also be a germicidal antimicrobial reticulated and/or open cell hydrophilic 1/4" foam, such as Aquazone with or without Frisby Technologies applied or Comfortemp. The second foam material is preferably backed with a nonwoven top sheet as mentioned

above. In fact, any of the foam materials discussed herein can be backed by such a nonwoven top sheet, but the nonwoven top sheet is not absolutely necessary. Also, many of the foam materials are interchangeable depending upon specific needs. Alternatively, the foam materials can be flame laminated to a non woven apertured top sheet of cotton, polypropylene or polyester, or a blend thereof, for example.

As shown in Figure 2, a third foam material 50, which provides support and has similar characteristics to the second foam material 30, allows the moisture vapors to continue their movement toward the outside. This third foam material 50 is a slow recovery moldable foam (by Poron or Foamex), a polyurethane reticulated and/or open cell hydrophilic antimicrobial foam or a spacer material that functions like a moldable foam and is composed of polypropylene and polyester and is formed in certain areas to take the shape of an ankle, heel pocket and foot bones. An air bladder may also be added in the area around the ankle in place of the third foam material 50 or in combination with the shaped foam to aid in performance and support. The air bladder may be inflated by pumping the reflective grip 410 just under the pull tab. Furthermore, spacer fabrics may also be used in place of the foam or bladder 50. The moldable polyester, polyamide, polypropylene spacer materials may be such as those manufactured by Müller, Schiebler, Peltzer or Fugafil or the like in varying combinations. The environmental acceptability of many foam materials is an important factor to consider when

selecting the proper materials. Material 50 is positioned so as to allow the moisture to pass through into subsequent elements, such as waterproof/breathable membrane 60 and the outer shell 70, or an encapsulated outer fabric of the overall lining system. The outer fabric may also be treated with a waterproof film and may or may not be encapsulated. The third foam material 50 can be designed to provide a well defined heel lift, and heel pocket. The pocket may also contain a silicon gel or the like. This invention enables improved performance with the increased support around the heel, toe and ankle. The toe box is from top to bottom, wider and more flexible than in previous liners, specifically those described in U.S. Patent Nos. 5,092,614 and 5,397,141. The laminated foams under the heel support the skaters lower back and allows for a comfortable stride. With this added comfort, the aggressive or recreational skater can achieve a higher level of continued performance.

As shown in Figure 3, between the supporting second foam material 30 and the third foam material 50 is a structural mesh 40 which can be a flex guard, for example such as one manufactured by NALTEX or Conwed Plastics, or the like, that adds structural integrity to the lining system. A moldable foam, spacer material or silicon gel or the like may also be used in place of this flex guard or an air bladder. The moldable foam may or may not be a slow recovery foam by Rogers or the like. If it is not very breathable, it can be made breathable by puncturing. Alternatively, the moldable foam is

preferably similar in construction to the second foam material, and can be a polyurethane reticulated and/or open-cell hydrophilic antimicrobial germicidal foams approximately 1/4 inch thick (for example, Aquazone, Netsorb, Comfortemp, or the like). A nonwoven top-sheet (with or without apertures) can be attached to the moldable foam. If a moldable foam or spacer fabric is used, then the second foam material may be omitted. Also, the moldable foam can be Aquazone.

As mentioned earlier, the third foam material 50 is preferably similar in construction to the second foam material, namely being either germicidal, reticulated and approximately 1/4 inch thick or being germicidal, hydrophilic, and open-cell (for example, Aquazone). This material is preferably laminated to a nonwoven top sheet (which may or not be apertured) comprised of wood pulp, rayon, cotton, polyester, polypropylene or a combination thereof. The top sheet abuts the waterproof/breathable membrane 60 or the encapsulated outer fabrics. The outer shell fabrics may also be treated with waterproof film and may be encapsulated or followed by a breathable membrane in some performance categories. The outer fabrics may also be constructed to repel water and breathe and may not need a waterproof membrane or encapsulation in some performance categories.

The moisture vapor continues from the second foam material 30 through the mesh 40 and on through the third exterior foam material 50. If the spacer fabrics are used then the outer layer of foam material 50 may be eliminated in

certain performance conditions. The moisture vapors are then passed through waterproof/breathable membrane 60 or the encapsulated outer fabrics, or the like. If the outer fabric is encapsulated, then the moisture vapors pass around the encapsulated fibers and onto the surface fabric. If the liner employs a waterproof/breathable membrane, then the moisture vapors are absorbed into the membrane and passed through to an outer layer of fabric 70, as shown in Figure 4. The waterproof/breathable membrane 60 can be selected from a variety presently available on the market. Those under the tradenames VAPEX 2000/PLUS/STANDARD/1300 , SECO-TEC, DERMIZAX, THINTECH, LAY-TEK, WITCOFLEX ECO DRY (by Baxenden Chemical), and PTFE by TETRATEC in combination with the Outlast membrane are currently being considered. However, the membrane currently being considered is TX-1540 distributed by Shawmut Mills. TX-1540 may or may not be in combination with the Outlast membrane which regulates temperature. If the preceding foam layers are Comfortemp or have Frisby Technology applied to the foam, then the Outlast member is eliminated. These waterproof/breathable membranes are ultra-thin, skin friendly, moisture barriers that allows moisture vapors to escape while preventing outside water from penetrating. Outlast, which is a membrane manufactured by Gateway Technologies or Frisby Technologies which is a thermabsorb microencapsulation technology can adjust to temperature changes.

A number of patents have been issued to Triangle Research & Development Corp. disclosing details related to the processes now being employed by Gateway Technologies and Frisby. For example, U.S. Patent Nos. 4,756,958 and 5,366,801 are directed to fibers and fabrics with reversible enhanced thermal properties, respectively. The disclosures of these two patents are hereby incorporated by reference. Other patents assigned to Triangle Research & Development Corp., that are related by subject matter and have overlapping inventorship, include U.S. Patent Nos. 5,415,222, 5,290,904, and 5,224,356. These patents are also hereby incorporated by reference.

Another patent, U.S. Patent No. 5,499,460, which has overlapping inventorship with the above-mentioned patents, is directed to a moldable foam insole with reversible enhanced thermal storage properties. The disclosure of this patent is hereby incorporated by reference, and is illustrative of one type of moldable foam that can be used as mentioned herein.

Also shown in Figure 4 is a protective rim or cuff 80, preferably made of neoprene covered by lycra. Also, a germicidal hydrophilic open cell and/or reticulated foam by Foamex or Vita Olympic, for example, can be used. A pull tab 90, preferably made of nylon, is connected to the protective rim 80. An abrasive protective material 100 is provided adjacent to a tongue 300. Another abrasive protective material 110 is provided around the heel portion of the shoe.

Abrasive protective material 110 is supplied by Schoeller or Dupont, for example.

The outer layer of fabric 70 of the lining system has 200 to 6000 denier strength and is made waterproof by a membrane, encapsulation technology or a waterproof film. If the waterproof film is applied to the outer fabric, then the membrane or encapsulation technology may be omitted.

Encapsulation technology is being utilized by company called Nectex, Inc. or Toray, Inc. (a Japanese company or the like). The breathable membranes preserve the outer layer of fabric 70 and perform as a waterproof barrier for the liners. If the encapsulation technology is applied to the outer layer of fabric 70, then the breathable laminate membranes need not be used. The encapsulation technology regulates the degree of waterproofness and breathability of the outer fabric shell by encapsulating an internal layer of fibers within the outer fabric. If the encapsulated fiber layer is closest to the fabric surface, the fabric is very waterproof and less breathable. If the layer is in the middle of the outer shell fabric, then the fabric is equally waterproofed and breathable.

The outer layer of fabric 70 is a combination of extremely durable, lightweight materials, kevlar/keprotec products 13207, 13624, 13632, 6500, 14705, 65563, 13602, 13408 (manufactured by Schoeller, Inc.), the Schoeller spirit line 14138, 14118, 14140, 14120, 14124, 14126, 14128, 14134, 14642, 14643, 14641, 14645, 14636, 14637, 14122, 14132, 14640, nylon

supplex (such as that manufactured by Travis Textiles, Inc. or Blank Textiles, Inc.), nylon cordora (manufactured by Schoeller, Inc.), other cordoras (manufactured by Schoeller or Dupont), maxus 6 ply (manufactured by Blank Textiles, Inc.) or starlite Dri-lex nylon fabric (manufactured by Faytex Corp.), Mojave or Tudor (both manufactured by Travis Textiles, Inc.), Microft (manufactured by Teijin), Entrant Gil and Dermizax (both manufactured by Toray), Gymstar Plus (manufactured by Unitika), Ultrex High Performance Fabrics (manufactured by Burlington, DuPont, Schoeller or the like), or the like, or other fabrics having similar characteristics as these new products. Also, the Typar nonwovens by Sontara Technologies can be used in combination with outer fabrics and are not to be confused with the nonwoven top sheets attached to the inner foam materials. Instead, this is a high abrasion, moisture transfer, absorbent material that is a spun lace (polypropylene) moisture management product, such as Sontara Technology nonwoven, manufactured by Dupont, for example.

Selecting the proper materials depends upon the needs of each individual skater. The non-abrasive cool fabrics used in the inner liner of the present invention greatly reduces the possibility of trapped moisture, thereby protecting the foot from fungus growth and any damage. The more aggressive skaters need a moisture transfer liner that can remove large amounts of moisture continuously from the foot. These skaters often do not wear socks and as a result, calluses, abrasions and blisters become commonplace. A wetting agent may be

applied to any of the inner lining materials 20 to enhance the moisture transfer away from the foot. The antimicrobial antifungal polypropylene (polyolefin) fabrics quickly remove moisture away from the foot. Skin damage is minimized because the polypropylene fabric has a smooth, continuous surface. This fabric also prevents bacterial build-up which can cause foot odor and fungus.

The looped polyester terry blend or the like is an excellent wicking fabric and can remove moisture rapidly. A wetting agent by Witco, or the like, may be applied to enhance wickability.

The antimicrobial, antifungal Dri-lex nylon fabrics, like the polypropylene, is sanded and soft. The material not only removes moisture from the foot, but also is extremely comfortable and cool to the touch.

The polyester field sensor fabric or the like works well with those individuals who prefer sports or recreational skating. This liner absorbs moisture immediately and is recommended for the soft boot inner liner.

Finally, polyester microfiber fabric is advantageous in that it is cool to the touch, smooth and wickable. A wetting agent treatment enhances wickability.

As a result of using this lining system, the skater continues to have a cooler, drier foot. The lightweight kevlar, starlite and cordura, or the like, outer liner materials are twice as durable as the former heavyweight nylons often used on the outer shell, but function as a softer

feeling breathable outer surface and aid in the moisture transfer.

Figures 5(a) and 5(b) illustrate a sole portion 200 of a foot foam pad covered with cambrelle Dri-lex nylon, or the like. Preferably, however, the foot pad is designed using Sontara Technology nonwoven, by Dupont, and called ComforMaxSPORT. ComforMaxSPORT, or the like, is backed by hydrophilic moldable foam and helps protect foot bed from rubbing due to friction. The inserted hydrophilic antimicrobial foam (an open cell moisture vapor transfer foam) or slow recovery punctured foam foot pad adds support and transfers moisture downward. The bottom portion of the foam is preferably provided with a nonwoven top sheet as described earlier, a material called Saran@Climate Insoles by Fugafil or Summuntex 1, 2 by Textel may also be used in place of the foam foot bedfoot. The heel pocket foam or gel protects the back of the heel with a double layered reticulated and/or slow recovery moldable foam. This cushion protector allows circulation in the heel. ComforMaxSPORT or an antimicrobial cambrelle Dri-lex nylon 210, or the like, covers a molded hydrophilic foam 220 that supports the arch and insures the skater a comfortable stride.

Figures 6, 7 and 8 illustrate the tongue 300 of the boot in more detail. The tongue is designed to add further comfort and support. As shown in Figure 8, an inner liner fabric 310 of the tongue 300 is preferably one of the other inner liner materials mentioned above, especially the polypropylene lycra

blend with INNOVA fiber, the polyester microfiber or the polyester looped terry or the like. This inner liner fabric 310 is preferably laminated to a structural support foam 320, which is preferably a $\frac{1}{4}$ inch antimicrobial reticulated and/or slow recovery punctured foams. A hydrophilic open cell or reticulated perforated foam 330 abuts a structural support foam 320. The hydrophilic open cell or the slow recovery perforated foams 330 can take the shape of the foot bones and protect the upper foot from damage. A moldable spacer material may also be used in combination with foam 330 or in some cases in place of the foam 330. The structural support 320 can also be shaped to accommodate the foot and protect the ankle bones. A moisture transfer material 340 lies over the outer edges of the hydrophilic perforated foam or combination foam and spacer material 330 and is connected to the inner liner 310 and underlies the outer protective polyurethane layer 350. This moisture transfer material 340 is preferably made from a material known as aero-spacer Dri-lex, which is manufactured by Faytex Corp, or an aero-spacer fabric manufactured by Apex Mills or the like. Optionally, a nonwoven material such as Sontara Technology manufactured by Dupont can be used.

The nonwoven material, Sontara Technology, is a spun lace moisture management product called Typar, for example. It can have a sanded surface treatment or it can look like steel wool and would wrap around the top of the tongue. It should be understood that these nonwoven materials can always

be substituted for the aero-spacer Dri-lex, even if not specifically mentioned in other parts of this disclosure. This material 340, is wrapped around the outer edge of the tongue to allow moisture vapors traveling from the upper foot area to escape through moisture transfer material 340 to the outer surface of the tongue 300. Material 340 also aids in providing a softer edged tongue. Finally, an outer protective polyurethane layer 350, or the like, is provided over a central portion of the material 340. Another hydrophilic open cell foam or slow recovery punctured foam (not shown) is shaped to fit between the outer protective polyurethane layer, cordura nylons, kevlar or synthetic breathable leathers (by Daewoo Corporation, for example) 350 or the like are surrounded by aero spacer Dri-Lex 340, or a substitute as mentioned above, or the like. The protective polyurethane layer may be optional in both the shell liner and the soft boot. If the protective polyurethane layer is omitted, then the slow recovery foam (not shown) or open cell foam may also be omitted.

As shown in Figure 6, polyurethane, kevlar fabrics or synthetic breathable leather layer (by Daewoo Corp. for example) 350 is surrounded by aero-spacer Dri-lex 340, or a substitute as mentioned above. At the top of the tongue 300 is an abrasive grip fabric 100 (such as a that is manufactured by Schoeller and identified by the number 6500), also shown in Figure 4. Stitching is identified by numeral 370. Figure 7 illustrates a top portion of the tongue 300, and shows

stitching 370 and the inner liner fabric 310. It is recommended that lycra and nylon thread such as those used by the Dupont Xymid Group or Tietex be used for these stitched areas or adhesive bonding by Applied Extrusion Technologies, or the like. In fact, adhesive bonding may be utilized in place of or in combination with several stitched areas on the outer liner fabrics.

In-line skate tongues have in the past been hard vinyl edged forms. The shape of these tongues often did not fit the skater's foot. Furthermore, vinyls may damage the upper foot where they meet the inner lining edge during active use of the in-line skate. As a result, the skater may develop blisters, calluses or bruises on this upper foot area. Additionally, the inner fabrics of the tongue liner have often been non-breathable nylon or vinyl, thereby increasing the possibility of foot bacteria fungus to develop.

The liners are preferably provided with a pull tab 90 as illustrated in Figures 4, 9 and 10 on the back of a cuff 80 constructed of neoprene or reticulated foam covered by lycra, or the like. Figure 9 shows an opened up version of the liner looking from the back of the shoe. The outer upper cuff, that is exposed above the shell of the in-line skate removable liner, is provided to protect a skater's leg from abrasion. Located just beneath the cuff 80 is a abrasive grip fabric material 410, such as that manufactured by Schoeller, Inc. and referred to by the number 6500, or the like. Below material 410 is a reflective grip material 420. Below the reflective

grip material 420 is a highly abrasive fabric 110, as shown in Figure 4. The reflective material 14209 by Schoellar may also be used as fabric 110. Fabric 110 is preferable a Kevlar by Toray-Dupont or Schoeller (Keprtec or Schoeller spirit) or the like, Starlite, cordura, or the like. Finally, outer shell fabric 70 is the same as that shown in Figure 4, and can be any of the fabrics listed previously in connection with outer shell fabric 70. The nylon pull tab 90 allows the skater to easily slip into the liner.

Figure 10 shows the other side of the liner of Figure 9. In Figure 10, 510 can be a 1/4 inch punctured moldable foam, spacer fabric or an air bladder of a similar shape. The foam and air bladder may also be used in combination. Alternatively, the moldable foam can be substituted by a reticulated or hydrophilic, open-cell foam or silicon gel or the like. A nonwoven top-sheet (with or without apertures) can be attached to the moldable foam. Also, a spacer material, such as that made by Müller or the like, can be used as material 510. 520 represents the combination of the flexible mesh (in the case the moldable foam is not used, as depicted), the breathable membrane and the outer shell fabric, or encapsulated outer shell fabric. As in all of the Figures, the arrows depict the flow of moisture.

Figure 11 illustrates the toe portion 400 of the shoe. Preferably, the toe portion 400 is constructed with an inner liner 10, followed by a foam material 30, followed by a breathable membrane 60 and finally followed by the outer

fabric 70 or encapsulated outer shell fabrics. Abrasive grip fabric 100 is also shown.

The 6500 high abrasive fabrics manufactured by Schoeller, Inc., or the like, are located on the back of the cuff and the top of the toe box, heel, and tongue grip area. The Kevlar and cordura starlite fabrics provide comfort and durability to the liners and are extremely strong and resistant to abrasion and allow for breathability and performance.

The microfiber technology disclosed above is rapidly developing and changing and has greatly increased the potential for improved performance of such products such as in-line skates, provided that they are properly utilized as in the present invention. These new products are part of rapidly developing fabric technology. The present invention employs a combination of fabrics, foam layers, nonwovens, spacer fabrics, breathable membranes, encapsulated technology, structural woven water repellent fabrics, or waterproof film coatings in such combinations that increase the performance of the products in which they are used as well as increase breathability. The waterproof/breathable membranes have also only recently developed and are believed to be less than ten years old.

It should be noted that, in the case of in-line skates, the lining system of the present invention can be applied to both shell boots and soft boots. The soft boot in-line skate, mentioned earlier in the Background of the Invention, addressed the needs of a skater to have more flexibility and

comfort yet still maintain performance levels. This new technology in the in-line skate industry has increased tremendously the possibilities of a lighter weight performance product. However, the soft boot in-line skate does not have any type of lining system that even remotely resembles the lining system of the present invention. The liner of the soft boot can be adapted to this new moisture transfer system.

While the soft boot does not have a protective shell, nor a removable liner, it can nonetheless be provided with a liner that enjoys all of the benefits of the liner according to the present invention. Preferably, the outer layer of the moisture transfer system for the soft boot application would be a starlite Dri-lex nylon, Kevlar, or high abrasion cordura fabric, such as that manufactured by Schoeller, or the like. These fabrics, as well as the high abrasive fabrics, are encapsulated or are provided with a waterproof/breathable membrane laminated to their back or are encapsulated. A reticulated and/or open cell hydrophilic antimicrobial germicidal $\frac{1}{4}$ " foam abuts the encapsulated outer fabric or breathable membrane. The structural mesh or molded spacer material is stitch bonded or laminated to the $\frac{1}{4}$ " reticulated or open cell hydrophilic foam. A slow recovery punctured foam or silicon gel, or the like, are located in the heel pocket is located both in the heel pocket, toe and tongue areas. An air bladder may also be added around the ankle areas to increase performance in some cases. The structural mesh or molded spacer materials abut a nonwoven top sheet that is laminated,

stitch or ultra sonically bonded to a reticulated and/or open cell hydrophilic $\frac{1}{4}$ " foam. The $\frac{1}{4}$ " foam abuts preferably a cellular elastomeric composite which is laminated to the inner fabric. A nonwoven top sheet laminated to $\frac{1}{8}$ " foam may also be used in place of the elastomeric composite. Also, instead of being removable, the liner would preferably be directly attached to the base of the soft boot by methods well known in the art, such as that disclosed in U.S. Patent No. 5,437,466. Substitutions can be made to all of the foam materials (ie. hydrophilic open cell, Aquazone, etc.) just as discussed earlier, and are not specifically repeated here. Other aspects of the present invention can be applied to the soft boot without any significant structural changes. The soft boot density is increased in the footbed, toe box, and heel plate. This added support provides, protection and assist in maintaining technical performance levels. The in-line soft boot breathability would be greatly enhanced with this added moisture transfer liner system. The soft boot may also employ the nonwoven top sheets in a number of combinations with the foam layers to increase moisture transfer.

Also, the soft boot outer shell may be a combination of synthetic breathable leather (such as that available from Daewoo, Inc. or the like), an encapsulated, waterproof film or breathable membrane outer fabric by Dupont, Schoeller, Burlington, Malden Performance Fabrics or any of the former fabrics mentioned, or the like, as well as synthetic rubbers, PVC, TPR or TPU, a thermoplastic composite material. Tygar

Nonwovens by Sontara Technologies, or the like, may be used in combination with the outer materials in high abrasion areas.

The outer shell combined materials are then laminated, stitched or ultrasonically bonded, or the like, to interior foam layers. An air bladder may be added in combination with or in place of the molded foam and structural mesh to aid in comfort and performance. If the internal layers of foam and nonwovens are stitch bonded, it is recommended that the process with lycra thread by the Xymid Group of Dupont be used or the process developed by Tietex with nylon thread, or the like. The outer shell fabric seams may be stitched or adhesively bonded.

The inner moisture transfer fabrics are any of the former fabrics listed, as suggested for the removable liner, or the like. The foam is either Aquazone, Vita Olympic, Netsorb, or the like, in combination with a nonwoven top sheet as mentioned or the foam-nonwoven combination may be replaced with a foam/top sheet composite referred to as a cellular elastomeric composite. Presently, this invention is considering the use of a breathable polyester and/or polypropylene filtering material produced by Vitafibers QW 110 - QW 150 quiet web or Tangerding Vliesstoffe (TH-FI 210 B or FF-FI 250). These materials may be substituted for the reticulated or open cell foams previously mentioned, materials 30 and 50 for example.

While the present invention has been described above in connection with the preferred embodiments, one of ordinary

skill in the art would be enabled by this disclosure to make various modifications to the disclosed embodiments and still be within the scope and spirit of the present invention as recited in the appended claims.

08897347-070397
/5E0/0" /4E/8880

What is claimed is:

1. A moisture transfer system comprising a plurality of layers arranged to transfer moisture in a predetermined direction, the moisture transfer system comprising:

an inner fabric layer;

an outer fabric layer positioned relative to the inner fabric layer in the direction of moisture flow, wherein moisture flows from the inner fabric layer through any intermediate layers and then through the outer fabric layer; and

at least one foam material positioned between the inner fabric layer and the outer fabric layer;

wherein the outer fabric layer is treated to have waterproof/breathable characteristics.

2. The moisture transfer system according to claim 1, wherein a wetting agent is applied to the inner fabric layer in order to increase moisture transfer.

3. The moisture transfer system according to claim 1, wherein the outer fabric layer is made waterproof by attaching a waterproof/breathable membrane thereto.

4. The moisture transfer system according to claim 1, wherein the outer fabric layer is made waterproof by employing encapsulation technology.

5. The moisture transfer system according to claim 1, wherein the outer fabric layer is made waterproof by application of a waterproof film.

6. The moisture transfer system according to claim 1, wherein the foam material is an antimicrobial, germicidal, reticulated foam that is backed by a nonwoven top sheet.

7. The moisture transfer system according to claim 1, wherein the foam material is an antimicrobial, germicidal, hydrophilic open-cell foam that is backed by a nonwoven top sheet.

The moisture transfer system includes a waterproof/breathable moisture transfer liner having an inner fabric layer selected from technically advanced fabrics which are carefully selected. A series of layers are provided outside the inner liner including foam material layers, breathable membranes, encapsulation technology, waterproof films and an outer fabric layer. The moisture transfer system is incorporated into in-line skate as either a removable liner for a shell boot or a liner for a softboot.




Fig. 1

08887847, 07/03/97




Fig. 2




Fig. 3




Fig. 4




Fig. 5(a)




Fig 5(b)

08887947.070387
25E020 24E/8880




Fig. 6




Fig. 7

09337847.020397




Fig. 8





Fig. 9

08987647, 070397

Fig. 10

08887847, 070397



08387847.070397




FIG. 11

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name. I believe I am the original, first and sole inventor (if only one name is listed below), or an original, first and joint inventor (if plural names are listed below), of the subject matter claimed and for which a patent is sought on the invention entitled:

WATERPROOF/BREATHABLE MOISTURE TRANSFER LINER FOR IN-LINE SKATES AND THE LIKE

the specification of which: (check one) ☒ [X] is attached hereto.

[] was filed on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information material to examination of this application according to Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application (s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

_____ (Application Number)	_____ (Filing Date)	_____ (Status -- patented, pending, abandoned)
_____ (Application Number)	_____ (Filing Date)	_____ (Status -- patented, pending, abandoned)

JUN 29 1997 2:04PM FSB ALEX

I hereby claim the benefit under Title 35, United States Code, Section 120, of any United States application(s) or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------------	---------------	--

(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------------	---------------	--

(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
--------------------------	---------------	--

I hereby appoint the following attorneys/agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith and with any divisional, continuation, continuation-in-part, reissue or re-examination application with full power of appointment and substitution of associate attorneys and agents, and to receive all patents which may issue thereon: Thomas E. Beall, Jr., Reg. No. 22,410; Joseph D. Dreher, Reg. No. 37,123; Christopher B. Fagan, Reg. No. 22,987; Jude A. Fry, Reg. No. 38,340; Jeffrey M. Ketchum, Reg. No. 31,174; Richard M. Klein, Reg. No. 33,000; Thomas E. Kocovsky, Jr., Reg. No. 28,383; Sandra M. Koenig, Reg. No. 33,722; Petar Kraguljac, Reg. No. 38,520; Scott A. McCollister, Reg. No. 33,961; James W. McKee, Reg. No. 26,482; Shrinath Malur, Reg. No. 34,663; John R. Mattingly, Reg. No. 30,293; Richard J. Minnich, Reg. No. 24,175; Jay F. Moldovanyi, Reg. No. 29,678; Philip J. Moy, Reg. No. 31,280; Timothy E. Nauman, Reg. No. 32,283; Sue Ellen Phillips, Reg. No. 32,046; Patrick R. Roche, Reg. No. 29,580; Albert P. Sharpe, III, Reg. No. 19,879; Daniel J. Stanger, Reg. No. 32,846; Eric A. Stephenson, Reg. No. 38,321; Gene W. Stockman, Reg. No. 21,021; Mark S. Svat, Reg. No. 34,261; John C. Tiernan, Reg. No. 21,078; John M. Vasuta, Reg. No. 38,353. Address all correspondence to: FAY, SHARPE, BEALL, FAGAN, MINNICH & MCKEE

[X] 104 East Hume Avenue
Alexandria, Virginia 22301 (703) 684-1120

[] 1100 Superior Avenue, Suite 700
Cleveland, Ohio 44114 (216) 861-5582

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, Section 1001, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date June 28 1997 Inventor Baychar

B. Baychar

(Typed Name and Signature)

Residence Snobrook 2506 Sugarloaf Mountain, Carrabassett Maine 04947

Citizenship United States

Post Office Address Same as Residence

Applicant ~~in Process~~: Baychar

Serial or Patent No.: _____

Attorney's BAY-210Filed ~~in Process~~: Concurrently HerewithTitle: WATERPROOF/BREATHABLE MOISTURE TRANSFER LINERFOR IN-LINE SKATES AND THE LIKE

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS

(37 CFR 1.9(d) & 1.27(b))--INDEPENDENT INVENTOR

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office regarding the invention entitled _____ described in:

☒ the specification filed herewith.☐ application serial number _____, filed _____☐ patent number _____, issued _____

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:*

☒ No such person, concern, or organization☐ Persons, concerns or organizations listed below*

* Note: Separate verified statements are required from each named person, concern or organization having rights to the invention availing to their status as small entities. (37 CFR 1.27)

NAME _____

ADDRESS _____

☐ INDIVIDUAL☐ SMALL BUSINESS CONCERN☐ NONPROFIT ORGANIZATION

NAME _____

ADDRESS _____

☐ INDIVIDUAL☐ SMALL BUSINESS CONCERN☐ NONPROFIT ORGANIZATION

NAME _____

ADDRESS _____

☐ INDIVIDUAL☐ SMALL BUSINESS CONCERN☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Baychar

NAME OF INVENTOR

* Baychar

Signature of inventor

* June 28 1997

Date

NAME OF INVENTOR

Signature of inventor

Date

NAME OF INVENTOR

Signature of inventor

Date